





AMERICAN FLOOR PRODUCTS COMPANY, INC.

AFCO-USA

P.O. BOX 7055 • Gaithersburg, Maryland 20898 -7055 • 301-987-0490 • Fax 301-987-0422
email: sales@afco-usa.com • Web Site: www.afco-usa.com

CUSTOMER P.O. #

AZTEC® Wall Guard (WG-2180) EXT



AZTEC[®] Wall Guard (WG-2180) *EXT*

Profile	Application	Shock absorbing	ADA Compliance	Materials	Flammability & smoke developed (ASTM E-84)
Sculpted	High abuse Med-high abuse	25.4 ft.lbs/in. ASTM D-256	Yes	Vinyl Aluminum	Class A

Testing in accordance with NFPA 255 (ASTM E 84):

Class A Flame Spread 0-25
 Smoke Development 0-450

<p>Features:</p> <ul style="list-style-type: none"> • Class A fire rating • Molded end caps • Molded outside corners • Stock length: 12'-0" (3658 mm) 	<p>Finishes:</p> <ul style="list-style-type: none"> • Manufacturer's standard colors • Custom colors available
--	---

Wall Guard designs conform to OSHA, ANSI Life Safety, NFPA, BOCA, UBC, BOMA, ICBO, SBCCI, American Disabilities Act Accessibility Guidelines and all National Building /Code requirements.

JOB NAME:	ITEMS	QUANTITY
JOB NUMBER:	Guard Length: 12 ft.	
CONTRACTOR:	Color:	
ARCHITECT:	End Cap:	
DEALER NAME:	Outside Corner:	
SIGNATURE: Date:	Spacer: (every 16 inches)	